



MEGASA



Environmental Product Declaration

EN ISO 14025:2010 / UNE 36904-1:2018 / EN 15804:2012+A2:2019

Hot-rolled steel section proceeding from an electric arc furnace

Issuing date: 04/09/2023

Modification date: 06/10/2023

Expiry date: 03/09/2028

The declared validity is subject to registration and publication on
www.aenor.com

Registration code: GlobalEPD 001-013 rev.1

GlobalEPD
A VERIFIED ENVIRONMENTAL DECLARATION

AENOR
Confía

INDEX

1	General information	p.4	4	Limits to the system, scenarios and additional technical information	p.10
1.1.	The organisation	p.4	5	Declaration of the environmental parameters of LCA and LCI	p.14
1.2.	Scope of the declaration	p.4	5.1.	Environmental impact parameters	p.14
1.3.	Life cycle and compliance	p.4	5.2.	Use of resources	p.16
1.4.	Differences when comparing with previous versions of the present EPD	p.5	5.3.	Categories of wastes	p.17
			5.4.	Output flows	p.18
2	The product	p.6	6	Additional environmental information	p.19
2.1.	Product identification	p.6	6.1.	Emissions to indoor air	p.19
2.2.	Product composition	p.6	6.2.	Emissions to soil and water	p.19
2.3.	Product characteristics	p.6	6.3.	Biogenic carbon content	p.19
3	Information relative to LCA	p.7	7	References	p.20
3.1.	Life cycle assessment	p.7			
3.2.	Scope of the study	p.7			
3.3.	Declared unit	p.8			
3.4.	Allocation criteria	p.8			
3.5.	Cut-off rule	p.8			
3.6.	Representativeness, quality and selection of data	p.9			

The declaration holder is responsible for the content and, throughout the period of validity, for keeping the supporting documentation that justifies the data and statements included.

AENOR is a founding member of ECO Platform, the European Association of Environmental Product Declaration Verification Programs.



Declaration Holder

MEGASIDER ZARAGOZA, S.A.U.
PTR José López Soriano
Avda. de José López Soriano, 100
50720 La Cartuja Baja - Zaragoza
ESPAÑA

☎ (+34) 976 466 171

🌐 www.megasa.com



LCA study

Abaleo S.L.
D. José Luis Canga Cabañes. c/ Poza
de la Sal, 8; 3º A. 28031 Madrid, España

☎ (+34) 639 901 043

✉ jlcanga@abaleo.es / info@abaleo.es

🌐 www.abaleo.es



Program administrator: GlobalEPD

AENOR Internacional S.A.U.
C/ Génova 6.28009 Madrid, España.

☎ (+34) 902 102 201

✉ aenordap@aenor.com

🌐 www.aenor.com

UNE 36904-1:2018

The European EN 15804:2012+A2:2019 Standard serves as the basis for the PCR.

Independent verification of the declaration and data in accordance with the EN ISO 14025:2010 Standard.

☐ Internal ☒ External

Verification body:



1 GENERAL INFORMATION

1.1. The organisation

The MEGASA GROUP is a family business specializing in the production and distribution of long steel products.

The Group has more than a thousand employees, distributed among its different production plants and distribution units in the Iberian Peninsula and France.

With an installed capacity of more than three million tonnes, MEGASA uses an electric arc furnace to produce a wide range of long steels: round section, wire rod, electrowelded mesh and merchant and structural sections.

In 2016, Megsider Zaragoza, S.A.U. joined the Megasa Group. Recently relocated to the outskirts of the city, it is in a strategic logistics situation in the northeast of the Iberian Peninsula with very good communications with the most outstanding industrial areas of the country, as well as with France.

This factory specializes in the production of merchant sections, with a wide range of dimensions and grades. It completes its offer with ribbed products and structural sections.



1.2. Scope of the declaration

This environmental product declaration describes environmental information relating to the life cycle of cradle-to-door production with options of the hot-rolled steel section made in an electric arc furnace by the MEGASA GROUP in its factory located at Avenida de José López Soriano, 100, 50007, Zaragoza, (Spain).

The role played by the product system under study is the production of hot-rolled steel section for use as a structural element in the construction sector.

1.3. Life cycle and compliance

The EPD has been developed and verified in accordance with the UNE-EN ISO 14025:2010, UNE 36904-1:2018 and UNE-EN 15804:2012+A2:2020 Standards.


Heading	Iron and Steel industry. Environmental Product Declarations. Product Category Rules. Steel products for structures. Part 1: Basic products.
Register / Version	UNE 36904-1:2018
Issuing date	2018
Administrator	AENOR

The EPD includes the life cycle stages indicated in Table 1-2. The EPD is of the cradle-to-door type with options.

System limits. Information modules considered

Product stage	A1	Supply of raw materials	X
	A2	Transport to factory	X
	A3	Manufacturing	X
Construction	A4	Transport to construction site	X
	A5	Installation / construction	MNE
Stage of use	B1	Use	MNE
	B2	Maintenance	MNE
	B3	Repairing	MNE
	B4	Replacement	MNE
	B5	Rehabilitation	MNE
	B6	Energy use in service	MNE
	B7	Water use in service	MNE
End of life	C1	Deconstruction / demolition	X
	C2	Transport	X
	C3	Waste treatment	X
	C4	Elimination	X
	D	Potential of reuse, recovery and/or recycling	X

X = Module included in the LCA; **NR** = Not relevant module; **MNE** = Module not evaluated



The EPD may not be comparable to those developed in other Programs or in accordance with other reference documents; in particular, it may not be comparable to Declarations not developed and verified in accordance with the UNE-EN 15804 Standard.

Similarly, EPDs may not be comparable if the data source is different (e.g., databases), not all relevant information modules are included, or they are not based on the same scenarios.

The comparison of construction products must be done with the same function, applying the same unit declared and at the level of the building (or architectural or engineering work), that is, including the behaviour of the product throughout its life cycle, as well as the specifications of section 6.7.2 of the UNE-EN ISO 14025 Standard.

1.4. Differences when comparing with previous versions of the present EPD

This version of the EPD is issued to correct a misprint in the MFR data of the C3 module.

2 THE PRODUCT

2.1. Product identification

The EPD is applicable to hot-rolled steel section for construction, produced in an electric arc furnace.

Sections are steel materials available in a wide range of designs, each with specific functions, whether for large projects or small constructions. There are different types of steel sections according to the shape, mechanical strength and function, which makes it possible to use them in many construction processes. The range manufactured comprises:

- **Merchant sections:** Angles, plates, U, round bars and square bars
- **Merchant sections:** UPN

CPC code: 4214 - Bars and rods, hot-rolled, of iron or steel.



2.2. Product composition

The manufacturer declares the following composition:

Product composition	% in weight
Post-consumer scrap	85 - 86 %
Pre-consumer scrap	14 - 15 %

During the product life cycle, no hazardous substances of the “Candidate List of Substances of Very High Concern (SVHC) for authorisation” was used in a percentage greater than 0.1% of the product weight.

2.3. Product characteristics

The chemical composition and remaining characteristics have been established in the different product Standards of application:

Normativa – Perfil

UNE-EN-1025	Hot-rolled steel products for structures
UNE-EN-10056	Equal and unequal leg angles of structural steel
UNE-EN 10058	Hot-rolled wide flat steel bars and rectangular steel bars for general purposes. Dimensions and tolerances on shape and dimensions
UNE-EN 10059	Hot-rolled square steel bars for general purposes. Dimensions and tolerances on shape and dimensions
UNE-EN 10060	Hot-rolled round steel bars for general purposes. Dimensions and tolerances on shape and dimensions
UNE 36525	Hot-rolled merchant steel U-sections. Dimensions and mass
UNE 36522	Hot-rolled (UPN) normal U-sections. Dimensions and mass
UNE-EN 10279	Hot-rolled steel U-sections. Dimensional, shape and mass tolerances



3 INFORMATION RELATIVE TO LCA

3.1. Life cycle assessment

The Report of life cycle assessment for the EPD relative to the steel products of MEGASA GROUP, dated July 2023, was elaborated by the company Abaleo S.L. with the databases Ecoinvent 3.9 (January 2023) and Environmental Footprint 3.1 and the SimaPro 9.5.0.0 software, which is the most updated version available when the LCA was prepared.

To prepare the study, the data from Zaragoza's plant (Spain) have been taken into account.


The LCA study followed both the recommendations and requirements of the international ISO 14040:2006, ISO 14044:2006, UNE 36904-1:2018 and UNE-EN 15804:2012+A2:2019 Standards.

3.2. Scope of the study

The scope of the EPD is the cradle-to-door production with options (modules A1-A3, A4, C and D) of the steel sections made by the MEGASA GROUP for use as structural systems in the construction sector.

The specific data of the manufacturing process comes from the Zaragoza plant (Spain), corresponding to the year 2022. The LCA does not include the following:

- All equipment with a service life superior to 3 years.
- The construction of plant buildings; other capital goods.
- Staff work travel; the staff's travel to or from work.
- Research and development activities.



3.3. Declared unit

The declared unit is one tonne of product, including its distribution packaging.

3.4. Allocation criteria

According to the criteria of the reference standard:

- › Where possible, the product system has been extended to avoid the allocation of environmental impacts of co-products.
- › When it was not possible to avoid the allocation, an allocation of the inputs and outputs of the system has been made (based on mass).

It has not been necessary to apply economic allocation criteria.

3.5. Cut-off rule

In accordance with the criteria of the reference standard, the gross weight/volume of all materials used in the manufacturing process has been included in the LCA, so that at least 99% of the weight of the product unit is obtained.

There has been no exclusion of either material or energy consumption.

3.6. Representativeness, quality and selection of data

To model the steel section manufacturing process of the MEGASA GROUP, the factory's production data for the year 2022 have been used, which is a period considered representative of an average production. The following data have been obtained from this factory: consumption of material and energy; emissions to air and discharges to water; distances from suppliers; waste generation and management.

When necessary, the Ecoinvent 3.9 (January 2023) and Environmental Footprint 3.1 databases have been used, which are the latest versions available at the time of the LCA. For the inventory data, the most up-to-date version of SimaPro 9.5.0.0 software available at the time of the study has been used to model the LCA and to calculate the environmental impact categories requested by the reference standard.

For the selection of the most representative processes, the following criteria have been applied:

- They had to be representative data of the technological development actually applied in the manufacturing processes. If case of no information available, representative data of an average technology have been chosen.
- They had to be geographical data as close as possible and, where appropriate, regionalized means.
- They had to be the most current data possible.

To assess the quality of the primary data of the production for the product under study, the criteria of semi-quantitative evaluation of the data quality proposed by the European Union in its Guide to the Environmental Footprint of Products and Organisations are applied. The results obtained are as follows:

- Very good integrity. Score 1.
- Good methodological suitability and coherence. Score 2.
- Very good temporal representativeness. Score 1.
- Very good technological representativeness. Score 1.
- Very good geographical representativeness. Score 1.
- Very low data uncertainty. Score 1.

According to the previous data, the Data Quality Rating (DQR) takes the following value: $7/6 = 1.17$, which indicates that the quality of the data is excellent.

To better understand the data quality assessment carried out, it is indicated that the score of each of the criteria varies from 1 to 5 (the lower the score, the more quality) and that the following table is applied to obtain the final score:

Overall Data Quality Rating (DQR)	Overall data quality level
≤ 1.6	Excellent quality
1.6 a 2.0	Very good quality
2.0 a 3.0	Good quality
3 a 4.0	Reasonable quality
> 4	Insufficient quality

4 LIMITS TO THE SYSTEM, SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION



The product system studied in the Life Cycle Assessment of the section produced by the MEGASA GROUP is cradle-to-door with options. The following steps of production were studied:

Module A1: Production of raw materials

This module includes the production process of raw materials, which considers:

- › Extraction of resources and production of raw materials.
- › Transport to the processing/production centres of raw materials.
- › Energy and fuel consumption during the production of raw materials.
- › The consumption of other resources (such as water), during the production of raw materials.
- › The generation of waste and emissions to the air and discharges to water and soil, during the production of raw materials.
- › The production of the electricity used in the manufacturing process.
- › The scrap enters the plant as a residue, where it is processed as a secondary raw material.

Module A2: Transport

The transport by lorry, ship and train of all raw materials has been considered from the production sites (suppliers) to the Megasa Group's plant in Zaragoza (Spain). The transport distances of the raw materials have been calculated based on the locations showing in the databases of the purchasing and sales departments. Scrap enters the plant as waste, so its transport corresponds to the previous product system.

Module A3: Manufacturing

At this stage, the consumption of auxiliary materials in the production (auxiliary materials and general plant consumption) has been considered; the production of the necessary packaging to distribute the product to customers and its transport to the plant; emissions to air and water, as well as transport to the manager of the waste generated during this stage of the life cycle. The following co-products are generated in the production process: black slag and mill scale

The transport distances of the waste have been calculated based on the locations showing in the databases of the purchasing and sales departments.



Module A4: Transport to the place of use

The transport of the finished product from the plant where the steel is made up to the customer has been considered, with data from the year 2022, distinguishing the means of transport used: lorry or ship.

Parameter		Quantity (per unit declared)
Litres of diesel	Lorry EURO 5 (max.weight authori. 15.79 t)	0.0451 l/tkm
	Ship	0.0026 l/tkm
Average distance	Lorry EURO 5	574.64 km
	Ship	1424.16 km
Load factor (including empty return)		50%
Bulk density of products transported		-
Useful capacity factor		-

Module C1 – Deconstruction / demolition

For the LCA it has been taken into account that the deconstruction modulus (C1) is not considered relevant for quantitative analysis. The consumption of material and energy for the deconstruction and extraction of the MEGASA GROUP's steel products are included in the framework of the building or civil works of which they form part.

Module C2: Transport to the place of waste treatment/recovery

It is considered that, at the end of its useful life, the product under study is transported to the point of waste management by road. The average transport of the scrap received by the MEGASA GROUP's plant, authorized as a waste treatment facility for recovery operations (R4 – recycling or recovery of metals and metal compounds), has been considered.

Module C3 – Waste treatment, and Module C4 – Waste elimination

The waste scenario considered establishes that the products under study are sent to recycling for the recovery of steel as a secondary material.



Parameter	Value (per unit declared)	
Demolition	The consumption of material and energy for the deconstruction and extraction of the Megasa Group's steel products are included in the framework of the building or civil works of which they form part.	
Recovery system, specified by type	0 kg for reuse.	
	1000 kg for recycling.	
	0 kg for energy recovery.	
Elimination, specified by type	0 kg for final disposal (landfill):	
Assumptions for scenario development (transport)	Transport of waste up to manager:	Lorry EURO 5: 264.44 km

Module D – Charges and benefits beyond the limit of the system

Module D includes the potential for reuse and recycling expressed as net charges and benefits relative to secondary material recovered when leaving the product system, calculating material substitution effects only for the resulting net output stream from the product stage; the secondary material used as input in the product stage (A1-A3) has been excluded, considering only the % of non-secondary raw material that reaches the waste conditions.

Life cycle assessment. - UNE EN 15804

Additional
information

A1 a A3			A4 a A5		B1 a B7							C1 a C4				D
Product stage			Stage of construction process		Stage of use							End-of-life stage				Charges and benefits beyond the limit of the system
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	MNE	MNE	MNE	MNE	MNE	MNE	MNE	MNE	X	X	X	X	X
Supply of raw materials	Transport	Manufacturing	Transport	Construction / installation process	Use	Maintenance	Repairing	Replacement	Rehabilitation	Energy use in service	Water use in service	Deconstruction, demolition	Transport	Waste treatment	Waste elimination	Potential of reuse, recovery and/or recycling
			Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	Sce-nario	

X: Module evaluated. / MNE: Module not evaluated.

5

DECLARATION OF THE ENVIRONMENTAL PARAMETERS OF LCA AND LCI

Environmental impact parameters for 1 tonne of steel section

Environmental impact parameters defined in the UNE-EN 15804 Standard

Steel sections. Unit declared: 1 tonne											
Parameter	Unit	A1	A2	A3	A1-A3	A4	C1	C2	C3	C4	D
GWP-total	kg CO2 eq	2.35E+02	4.41E+00	1.07E+02	3.47E+02	1.27E+02	0.00E+00	4.09E+01	0.00E+00	0.00E+00	0.00E+00
GWP-fossil	kg CO2 eq	2.35E+02	4.41E+00	1.07E+02	3.46E+02	1.27E+02	0.00E+00	4.09E+01	0.00E+00	0.00E+00	0.00E+00
GWP-biogenic	kg CO2 eq	3.57E-01	2.58E-04	9.34E-02	4.51E-01	7.47E-03	0.00E+00	2.41E-03	0.00E+00	0.00E+00	0.00E+00
GWP-luluc	kg CO2 eq	1.60E-01	8.98E-05	1.61E-02	1.76E-01	2.51E-03	0.00E+00	8.00E-04	0.00E+00	0.00E+00	0.00E+00
ODP	kg CFC-11 eq	9.53E-06	9.36E-08	5.92E-07	1.02E-05	2.73E-06	0.00E+00	8.82E-07	0.00E+00	0.00E+00	0.00E+00
AP	mol H+ eq	8.28E-01	1.87E-02	7.46E-02	9.21E-01	3.83E-01	0.00E+00	1.06E-01	0.00E+00	0.00E+00	0.00E+00
EP-freshwater	kg P eq	6.12E-03	3.44E-06	3.79E-04	6.50E-03	9.94E-05	0.00E+00	3.21E-05	0.00E+00	0.00E+00	0.00E+00
EP-marine	kg N eq	1.63E-01	6.20E-03	1.00E-01	2.69E-01	1.42E-01	0.00E+00	4.16E-02	0.00E+00	0.00E+00	0.00E+00
EP-terrestrial	mol N eq	1.82E+00	6.66E-02	3.75E-01	2.26E+00	1.51E+00	0.00E+00	4.41E-01	0.00E+00	0.00E+00	0.00E+00
POFP	kg NMVOC eq	8.07E-01	2.32E-02	3.09E-01	1.14E+00	5.68E-01	0.00E+00	1.72E-01	0.00E+00	0.00E+00	0.00E+00
ADP-minerals&-metals 2	kg Sb eq	5.02E-05	1.46E-07	7.78E-06	5.82E-05	4.34E-06	0.00E+00	1.41E-06	0.00E+00	0.00E+00	0.00E+00
ADP-fossil 2	MJ, v.c.n.	4.48E+03	5.80E+01	2.08E+02	4.75E+03	1.67E+03	0.00E+00	5.40E+02	0.00E+00	0.00E+00	0.00E+00
WDP 2	m3 eq	1.02E+02	5.28E-02	5.80E+01	1.60E+02	1.53E+00	0.00E+00	4.93E-01	0.00E+00	0.00E+00	0.00E+00

- 
- › **GWP-total.** Global warming potential.
 - › **GWP-fossil.** Global warming potential of fossil fuels.
 - › **GWP-biogenic.** Biogenic global warming potential.
 - › **GWP-luluc.** Global warming potential of land use and land-use changes.
 - › **ODP.** Stratospheric ozone depletion potential.
 - › **AP.** Acidification potential, accumulated surplus.
 - › **EP-freshwater.** Eutrophication potential, fraction of nutrients reaching the final freshwater compartment.
 - › **EP-marine.** Eutrophication potential, fraction of nutrients reaching the final seawater compartment.
 - › **EP-terrestrial.** Eutrophication potential, accumulated surplus.
 - › **POFP.** Potential for formation of photochemical oxidants.
 - › **ADP-minerals&metals.** Abiotic resource depletion potential for non-fossil resources.
 - › **APD-fossil.** Abiotic resource depletion potential for fossil resources.
 - › **WDP.** Water deprivation potential (user), water weighted deprivation consumption.

Additional parameters of environmental impact defined in the UNE-EN 15804 Standard

Steel sections. Unit declared: 1 tonne											
Parameter	Unit	A1	A2	A3	A1-A3	A4	C1	C2	C3	C4	D
PM	Incidencia de enfermedades	1.58E-05	2.84E-07	1.80E-06	1.79E-05	8.39E-06	0.00E+00	2.73E-06	0.00E+00	0.00E+00	0.00E+00
IRP ¹	kBq U235 eq	6.20E+01	9.13E-03	4.17E-01	6.24E+01	2.67E-01	0.00E+00	8.64E-02	0.00E+00	0.00E+00	0.00E+00
ETP-fw ²	CTUe	6.60E+02	2.60E+01	2.17E+02	9.03E+02	7.48E+02	0.00E+00	2.41E+02	0.00E+00	0.00E+00	0.00E+00
HTP-c ²	CTUh	1.12E-06	3.25E-10	7.92E-07	1.91E-06	8.92E-09	0.00E+00	2.83E-09	0.00E+00	0.00E+00	0.00E+00
HTP-nc ²	CTUh	1.11E-06	3.00E-08	4.61E-06	5.75E-06	8.86E-07	0.00E+00	2.88E-07	0.00E+00	0.00E+00	0.00E+00
SQP ²	Pt	6.13E+02	1.09E-01	7.11E+02	1.32E+03	3.19E+00	0.00E+00	1.03E+00	0.00E+00	0.00E+00	0.00E+00

- **PM.** Potential incidence of diseases due to emissions of particulate matter.
- **IRP.** Human potential exposure efficiency relative to U235.
- **ETP-fw.** Comparative potential of toxic unit for ecosystems - freshwater.
- **HTP-c.** Comparative potential of toxic unit for ecosystems - carcinogenic effects.
- **HTP-nc.** Comparative potential of toxic unit for ecosystems - non-carcinogenic effects.
- **SQP.** Soil quality potential index.

Note 1

This impact category deals primarily with the eventual impacts of low doses of ionizing radiation on human health from the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents or occupational exposure due to the disposal of radioactive waste in underground facilities. The potential for ionizing radiation of the soil, due to radon or building materials, is not measured in this parameter either

Note 2

The results of this environmental impact indicator should be used with caution as the uncertainties of the results are high and experience with this parameter is limited.

Use of resources for 1 tonne of steel sections

Steel sections. Unit declared: 1 tonne											
Parameter	Unit	A1	A2	A3	A1-A3	A4	C1	C2	C3	C4	D
PERE	MJ, v.c.n.	3.35E+02	1.50E-01	1.06E+01	3.46E+02	4.40E+00	0.00E+00	1.43E+00	0.00E+00	0.00E+00	0.00E+00
PERM	MJ, v.c.n.	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ, v.c.n.	3.35E+02	1.50E-01	1.06E+01	3.46E+02	4.40E+00	0.00E+00	1.43E+00	0.00E+00	0.00E+00	0.00E+00
PENRM	MJ, v.c.n.	2.74E-02	1.15E-05	4.58E+01	4.58E+01	2.22E-04	0.00E+00	5.92E-05	0.00E+00	0.00E+00	0.00E+00
PENRE	MJ, v.c.n.	7.32E+03	5.83E+01	2.24E+02	7.60E+03	1.68E+03	0.00E+00	5.43E+02	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ, v.c.n.	7.32E+03	5.83E+01	2.70E+02	7.65E+03	1.68E+03	0.00E+00	5.43E+02	0.00E+00	0.00E+00	0.00E+00
SM	kg	1.16E+03	0.00E+00	0.00E+00	1.16E+03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	MJ, v.c.n.	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	MJ, v.c.n.	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	2.13E+00	2.44E-03	1.53E+00	3.66E+00	7.06E-02	0.00E+00	2.28E-02	0.00E+00	0.00E+00	0.00E+00

- **PERE.** Use of renewable primary energy excluding renewable primary energy resources used as raw material.
- **PERM.** Use of renewable primary energy used as raw material.
- **PERT.** Total use of renewable primary energy.
- **PENRE.** Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw material.
- **PENRM.** Use of non-renewable primary energy used as raw material.

- **PENRT.** Total use of non-renewable primary energy.
- **SM.** Use of secondary materials.
- **RSF.** Use of renewable secondary fuels.
- **NRSF.** Use of non-renewable secondary fuels.
- **FW.** Net use of running water resources.

Categories of wastes for 1 tonne of steel sections

Parameters describing the generation of residue.

Steel sections. Unit declared: 1 tonne											
Parameter	Unit	A1	A2	A3	A1-A3	A4	C1	C2	C3	C4	D
HWD	kg	1.66E-02	3.79E-04	1.94E-03	1.89E-02	1.11E-02	0.00E+00	3.58E-03	0.00E+00	0.00E+00	0.00E+00
NHWD	kg	2.26E+01	2.91E-03	9.62E+00	3.22E+01	8.33E-02	0.00E+00	2.68E-02	0.00E+00	0.00E+00	0.00E+00
RWD	kg	3.98E-02	4.87E-06	2.81E-04	4.00E-02	1.43E-04	0.00E+00	4.66E-05	0.00E+00	0.00E+00	0.00E+00

➤ **HWD.** Hazardous wastes eliminated.

➤ **NHWD.** Non-hazardous wastes eliminated.

➤ **RWD.** Radioactive wastes eliminated.

Output flows for 1 ton of steel sections

Parameters describing the output flows.

Steel sections. Unit declared: 1 tonne											
Parameter	Unit	A1	A2	A3	A1-A3	A4	C1	C2	C3	C4	D
CRU	kg	0.00E+00	0.00E+00	6.03E+01	6.03E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR	kg	0.00E+00	0.00E+00	3.73E+01	3.73E+01	0.00E+00	0.00E+00	0.00E+00	1.00E+03	0.00E+00	0.00E+00
MER	kg	0.00E+00	0.00E+00	8.60E-02	8.60E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EE	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

➤ **CRU.** Components for their reuse.

➤ **MFR.** Materials for recycling.

➤ **MER.** Materials for energy valuation

➤ **EE.** Exported energy.

6 ADDITIONAL ENVIRONMENTAL INFORMACIÓN



6.1. Emissions to indoor air

The manufacturer declares that the steel products under study do not generate emissions to indoor air during their useful life.

6.2. Emissions to soil and water

The manufacturer declares that the steel products under study do not generate emissions either to soil or to water during their useful life.

6.3. Biogenic carbon content

The manufacturer declares that the steel products under study do not include materials with biological content.

The packaging with biogenic carbon used to distribute MEGASA's product is less than 1% of the weight of the product. Following the indications of the reference standard, the declaration of the biogenic carbon content of the packaging is omitted because the mass of the materials containing biogenic carbon in the packaging is less than 5% of the total mass of the product.

7 REFERENCES

- › UNE-EN 36904-1 Standard. Iron and Steel industry. Environmental Product Declarations. Product Category Rules. Steel products for structures. Part 1: Basic products. 2018.
- › UNE-EN 15804:2012+A2:2019. Sustainability in construction. Environmental Product Declarations. Basic product-category rules for construction products.
- › General rules of the GlobalEPD program, 2nd revision. AENOR. February 2016.
- › UNE-EN ISO 14025:2010 Environmental labels. Environmental Declarations, type III. Principles and procedures (ISO 14025:2006).
- › UNE-EN ISO 14040:2006/A1:2021. Environmental Management. Life cycle assessment. Principles and reference framework. Modification 1. (ISO 14040:2006/Amd 1:2020).
- › UNE-EN ISO 14044:2006/A1:2021 Standard. Environmental Management. Life cycle assessment. Requirements and guidelines. Modification 2. (ISO 14044:2006/Amd 2:2020).
- › Report of life cycle assessment for the EPDs relative to the MEGASA GROUP's steel products. Drafted by Abaleo S.L, August 2023. Version 2.
- › Databases: Ecoinvent 3.9.1 (January 2023) and Environmental Footprint 3.1.
- › Environmental impact assessment methodologies implemented through SimaPro 9.5.0.0





MEGASA

Environmental Product Declaration

GlobalEPD
A VERIFIED ENVIRONMENTAL DECLARATION

AENOR
Confía